


J60 SERIES



MODULAR JACK CONNECTORS: 4 PORT RJ45, TAB DOWN RIGHT ANGLE PCB
MOUNT, SHIELDED, 6.35mm FOOTPRINT

Features:

- Top performance for high speed networking, voice and data applications
- Meet FCC PART 68, Subpart F requirements
- Advanced EMI/RFI protection with grounding options (PCB or panel)
- Available in Tab-down
- Applications: Telecommunications, Broadcast, Data Products
- RoHS Compliant



Specifications:


Insulator Material	PBT or Nylon
Contact Material	Phosphor Bronze
Contact Plating	Gold Plating on contact area and Tin Plating on tails with Nickel underplating all over
Current Rating	1.5 amps @25°C
Voltage Rating	125 V AC
Contact Resistance	20 milliohms maximum
Dielectric Withstanding Voltage	1000 V AC
Insulation Resistance	500 megohms minimum
Durability	750 cycles minimum
Operating Temperature	-40°C to +85°C
Wave Soldering Process	260°C ± 5°C, 5~10 Seconds

Ordering Code:

EXAMPLE PART NUMBER: **J60048822P00101**

SERIES:
RJ MODULAR JACK

HOUSING TYPE:
60-



NO. OF PORTS:
04 - 4 PORT

NO. OF CONTACTS PER PORT:
88 - 8P8C
11-10P10C

CONTACT PLATING:
2 - GOLD FLASH
3 - 15 MICROINCHES OF GOLD
6 - 30 MICROINCHES OF GOLD
9 - 50 MICROINCHES OF GOLD

CONTACT TAIL TYPE:
2 - RIGHT ANGLE PCB

HOUSING MATERIAL:
P - PBT
N - NYLON

MOUNTING OPTIONS:

1 - BOARD LOCKS

PORT TYPE:

0 - SINGLE ROW (TAB DOWN)

SHIELDING:

1 - METAL SHIELD

RIGHT LED COLOR:

0 - NO LED

LEFT LED COLOR:

0 - NO LED